

509.00 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications](#)

| | |
|---|---|
| Chip | Broadcom |
| Dimensions | 140x138x60mm |
| Certifications&Safety | CE, FCC, ROHS |
| I/O Ports | 8x 10/100/1000BaseT(X) 4x 1000 BaseSFP RS-232(RJ45) Console port LED: Power, port speed, port connection |
| Management | Support WEB Interface IEEE802.3 10Base-T Ethernet standard IEEE802.3u 100Base-TX/FX IEEE802.3z 1000Base-X IEEE802.3ab 1000Base-T(X) IEEE802.3x Flow control |
| Standards | IEEE802.1d STP IEEE802.1w RSTP IEEE802.1s MSTP IEEE802.1p QoS IEEE802.1ad QinQ |
| Network interface / Wire specifications | 10BASE-T: Category 3 and above non-mask / mask twisted pair (<=100 m) 100BASE-TX: Category 5 and above non-mask / mask twisted pair (<=100 m) 1000BASE-T: Category 5 and above non-mask / mask twisted pair (<=100 m) |
| PoE Support | No |
| Power input / consumption | Input voltage 12-36VDC Reverse connection protection Power interface : 5pin terminal |
| Operating temperature | -40~75°C |
| Cooling | Fanless |
| MTBF | 100.000hrs |