

609.00 EUR  
incl. 19% VAT, plus [shipping](#)



**Support:**  [Specifications](#)

|   |   |
|---|---|
| Chip                                    | Broadcom  |
| Dimensions                              | 140x138x60mm  |
| Certifications&Safety                   | CE, FCC, ROHS   |
| I/O Ports                               | 8x 10/100/1000BaseT(X)<br>4x 1000 BaseSFP<br>RS-232(RJ45) Console port<br>LED: Power, POE, port speed, port connection  |
| Management                              | Support WEB Interface<br>Support SNMP v1/v2/v3  |
| Standards                               | IEEE802.3 10Base-T Ethernet standard<br>IEEE802.3u 100Base-TX/FX<br>IEEE802.3z 1000Base-X<br>IEEE802.3ab 1000Base-T(X)<br>IEEE802.3x Flow control<br>IEEE802.1d STP<br>IEEE802.1w RSTP<br>IEEE802.1s MSTP<br>IEEE802.1p QoS<br>IEEE802.1ad QinQ |
| Network interface / Wire specifications | 10BASE-T: Category 3 and above non-mask / mask twisted pair (<=100 m)<br>100BASE-TX: Category 5 and above non-mask / mask twisted pair (<=100 m)<br>1000BASE-T: Category 5 and above non-mask / mask twisted pair (<=100 m)                     |
| PoE Support                             | PoE standard: IEEE802.3af, IEEE802.3a<br>Each port provides 15.4W, maximum 30W<br>Pin Definition: V+ (RJ4S Pin 1, 2), V- (RJ4S Pin 3, 6)<br>PoE Management: Support port-based PoE status display and PoE switch control                        |

|                           |   |
|---------------------------|---|
| Power input / consumption | Input voltage 45-60VDC<br>Redundant dual power input<br>Reverse connection protection<br>Power interface : 5pin terminal<br>Power supply : 140W (max) |
| Operating temperature     | -40~75°C  |
| Cooling                   | Fanless   |
| MTBF                      | 100.000hrs  |