



589.00 EUR
incl. 19% VAT, plus [shipping](#)

- USB Type C 2.0 OTG !
- 64GB eMMC !
- GPS ! Bluetooth ! WiFi !
- Android 14 !

Support:  [Specifications](#) | [API-Pack](#)

CTFPND-11C is designed as a mobile terminal for fleet management systems and adopted for other applications. Whether field service, SaaS provider, solution provider, warehouse operator or construction contractor, it is well designed for all industrial applications.

Truck drivers use it for navigation, routing, dispatch, electronic signatures, proof of delivery, order management, vehicle maintenance, fuel consumption management, logbook and fleet operators use it for ELD and extend digital workflow to mobile vehicles to improve productivity.

The CTFPND-11C is a high-performance tablet with 8-inch display and IP67 protection. Equipped with an octa-core processor, advanced GPS chipset, 4G/3G/Wi-Fi module, as well as RFID, Bluetooth, camera and support hardware customization.

Supports MDM remote control server. Supports OTA upgrades, firmware customization, APK integration and debug log.

- High performance media tablet with rugged design with IP67 rating
- Rear Camera 20MP
- 8" capacitive multi touch screen tablet for great mobility

- True HD 1080P Video Playback & Output
- High capacity battery for an entire days use
- Android 14 support
- GPS/WLAN/BT/2G/3G/4G(LTE)
- NFC
- Serial port (RS232)

Hardware

| | |
|-------------------------------|--|
| Dimension | 227x156x22mm, 825g |
| CPU Processor Speed | 2.0Ghz Octa Core |
| OS | Android 14 |
| Memory | 4GB RAM |
| Stoorage | 64GB NAND Flash |
| Memory Slot | micro SD Cardslot (up to 512GB) |
| GPS Chipset | GPS, GLONASS, GALILEO |
| Color Display | 8" TFT multi touch capacitive touchscreen |
| Panel Resolution | 1280 x 800 |
| Speaker | Yes |
| Antennas | Internal |
| Radio Frequency | 2G-GSM: 850,900, 1800, 900MHz 3G-WCDMA: B1, B2, B4, B5, B8 4G-LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B17, B20, B28, B66 4G-LTE TDD: B40, B38, B41 |
| Camera | 20MP rear |
| Light Sensor | Ambient Light |
| Motion Sensor | Accelerometer, E-Compass, Gyroscope |
| Wireless Interface | WLAN (802.11 a/b/g/n/ac; 802.11 d/e/h/i/j/k/r/v/w + BT V5.0 5GHz: 802.11a/n/ac — up to 500 Mbps; 2.4GHz: 802.11b/g/n — up to 144Mbps WFA WPA/WPA2 Personal, AES-CCMP, WPI-SMS4, GCMP, WPS2.0, WAPI (hardware) |
| LED | Two-color LED (Red/Green) |
| Operating voltage | 12V input |
| Battery | Built-In (6300mAh, Standy 1 week, ~6hrs operating) |
| IP Standard | IP67 |
| Betriebs- und Lagertemperatur | -20 bis 60°C |
| I/O ports | Storage: -20■ to 70■ 1x USB2.0 Typ-C (Data + power) 1x3.5mm Audio Headphone Jack 1x SIM card slot 1x Mini USB 2.0 OTG on the cradle 1x 8" Android TabletPC 1x Cradle |
| Lieferumfang | 1x RAM Mount 1x USB Cable 1x AC USB Adapter |