



569.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel N150 4 Core !
- 4GB RAM Onboard !
- 2x LAN !
- 1x COM !

- Intel® Twin Lake N150 (4C) Processor
- 1 x LPDDR5-4800 (4GB)
- 1 x eMMC (64GB)
- 2 x Realtek RTL8111H-CG 1 GbE
- 1 x M.2 B Key, 1x Nano SIM, 1 x M.2 E Key slot
- 3 x USB 3.2 Gen2 and 1 x USB Type C
- 1 x HDMI, 1 x COM port
- 1 x TPM 2.0
- 8V~26V wide voltage power input

SYSTEM

PROCESSOR	Intel® Twin Lake N150(4C) Processor
CHIPSET	Intel® SoC Integrated
SYSTEM MEMORY	Indsutrial grade LPDDR5 4800MHz onboard type(4GB), 8533MB/s
GRAPHICS	Intel® UHD Graphics
STORAGE	1 x Industrial grade eMMC (64GB), 400MB/s
DISPLAY INTERFACE	USB type C (DP 1.2) / HDMI 1.4 2 x Realtek RTL8111H-CG 1GbE, Option: 1x supports 802.3af and 802.3at PoE LAN(PD-Max: 25.5W, PSE-Max: 35W)
ETHERNET	Nuvoton NCT5225D
I/O CHIPSET	Nuvoton NPCT760AABYX
TPM	TPM2.0
FRONT I/O	3 x USB 3.2 Gen2 / 1 x USB 3.2 type C (Support display(5V/3A) and audio) / 2x RJ45 (1x POE option for PD mode or PSE mode) / 1 x HDMI 1.4 (Vertical) 1 x Power button / 1 x Terminal block 2pin with locked / 1x 5Px2 NP9 header as RS232/422/485
LEFT SIDE I/O	1x SIM slot hole for Nano SIM card / 2 x DIN rail hole
REAR SIDE I/O	M.2 2242 / 3042 B key (USB2.0, SATAIII, PCIe1) with nano SIM slot /M.2 2230 E key (PCIex1, USB2.0)
EXPANSION SLOT	
WATCHDOG TIMER	1~255 steps by software program

POWER REQUIREMENT

POWER INPUT	DC-in 8~26V (Default ATX mode, AT/ATX adjusting by BIOS)
POWER ADAPTER	Optional DC12V / 5A / AC / DC / 60W adapter (For AC SKU)
ANTENNA	4 x SMA Antenna (Optional for WiFi / LTE function)

MECHANICAL

THERMAL DESIGN	Fanless
MOUNTING	Din Rail Mount, VESA Mount (75 x 75mm) for option
DIMENSIONS (W X D X H)	118.5 x 80.4 x 39.5mm
MATERIAL	Enclosure: Die Casting

ENVIRONMENTAL	OPERATING TEMPERATURE	-25 ~ 55°C with 0.7m/s Air Flow (w/ Wide Temp. SSD/RAM)
	STORAGE TEMPERATURE	-40 ~ 85°C (-40 ~185°F)
	OPERATING HUMIDITY	10% ~ 95% R/H (Non-condensing)
	VIBRATION RESISTANCE	Operating: 5Hz~500Hz / 2Grms / 3Axis (w/ SSD, according to IEC60068-2-64)
	SHOCK RESISTANCE	Operating: 50 Grms, Half-sine 11 ms Duration (w/ SSD, according to IEC60068-2-27)
OS	CERTIFICATION	CE / FCC Class B
	OS SUPPORT	Windows® 11 64-bit / Windows® 10 64-bit / Ubuntu 24.04 / Linux (support by request)
PACKING LIST	PACKAGE	1 x Quick Installation Guide / 1 x Embedded System / 1 x Screws kit / 1 x 2 pin Terminal Block Male Connector / 1 x DIN-Rail Mount Bracket / 1x VESA Mount Bracket (BOM option) / 1 x COM port cable